



PRO-COM150-HDAR-3/...

3-Channel 19

- An integrated single tray combining solution housing a 3-channel hybrid TX hybrid combiner, duplex filter, active RX multicouplers and preselector.
- Minimal rack space required - only 3 HU.

DESCRIPTION

- Compatible with digital 6.25 kHz channel spacing.
- Single TX isolators fitted as standard (dual isolators available as option).
- 4 RX ports as standard.
- Please specify TX / RX frequencies when ordering.

ORDERING DESIGNATIONS

TYPE	PRODUCT NO.
PRO-COM150-HDAR-3/l	210002050
PRO-COM150-HDAR-3/h	210002002
ACCESSORIES	
ADAPTOR AC/DC 12V EU	240000040
ADAPTOR AC/DC 12V UK	240000041

c

ELECTRICAL	
MODEL	PRO-COM150-HDAR-3/...
FREQUENCY RANGE	l: 136 - 156 MHz h: 152 - 175 MHz
MAX. INPUT POWER PER CH	35 W
MAX. TX-TX SPACING, Δ TX	1.5 MHz
MIN. TX-RX SPACING	4 MHz
INSERTION LOSS - TX PATH	< 7.0 dB
TX-TX ISOLATION	> 70 dB
ANT-TX ISOLATION	> 40 dB @ 25° C
RX ISOLATION IN TX	> 80 dB
TX-TX spacing < 0.5 MHz	> 60 dB
TX-TX spacing > 0.5 MHz	
TX ISOLATION IN RX	> 80 dB
RX-RX spacing < 0.5 MHz	> 60 dB
RX-RX spacing > 0.5 MHz	
RX-RX ISOLATION	> 20 dB
IMPEDANCE	Nom. 50 Ω
SWR	≤ 1.5
LNA NOISE FIGURE	< 3.5 dB
GAIN - RX PATH	1 dB +/- 1 dB (factory set)
CURRENT CONSUMPTION	500 mA @ 12 VDC
MECHANICAL	
TEMP. RANGE	-30° C → +60° C
CONNECTORS	N-female
DIMENSIONS	19" x 3 HU x 500 mm (483 x 133 x 500 mm)
WEIGHT	Approx. 7.0 kg

ADAPTOR AC/DC 12V EU





ADAPTOR AC/DC 12V UK

